

# Sikafloor® Level PRO Primer

High quality, latex based liquid used for priming

<b>Product Description</b>	Sikafloor® Level PRO Primer is a latex based liquid, which can be used for priming a wide range of substrates prior to the use of Sika® Ceram adhesives and water based waterproofing membranes, self-levelling compounds. Sikafloor® Level PRO Primer will eliminate dust and reduce porosity of plasterboard, fibrous cement sheeting, cement render and porous concrete porous concrete
<b>Uses</b>	<ul style="list-style-type: none"><li>■ Porous concrete</li><li>■ Sand and cement screeds</li><li>■ Cement render</li><li>■ Fibrous cement sheeting</li><li>■ Plasterboard</li></ul>
<b>Characteristics / Advantages</b>	<ul style="list-style-type: none"><li>■ Suitable for internal and external use</li><li>■ Reduces porosity of substrate</li><li>■ Eliminates dust</li><li>■ Extends open time of adhesives</li><li>■ Easy application - ready to use no mixing required</li></ul>
<b>Storage and Shelf Life</b>	Approximately twelve (12) months from date of manufacture when stored in its unopened original containers in a cool, dry place.
<b>Instruction for Use</b>	
<b>Surface Preparation</b>	All surfaces must be totally sound, clean, dry and free from any loose particle or contamination such as grease, oil, paint, sealers, release agents and curing compounds. All concrete substrates must be porous, have a wood float finish, and be cured for a minimum of 28 days. Sand/cement screeds and renders must conform with the appropriate standard and should be left with a wood float finish and left to cure for at least 7 days per 25mm. Fibrous cement sheeting & plasterboard must be installed in accordance with the manufacturers specification.

Construction



<b>Application</b>	Sikafloor Level PRO Primer should be stirred before use. Sikafloor Level PRO Primer must be applied onto the correctly prepared substrate using a brush or roller.
<b>Coverage</b>	1 litre of Sikafloor Level PRO Primer will cover approximately 6-8m <sup>2</sup> . Coverage may vary depending on substrate porosity.
<b>Drying</b>	Sikafloor Level PRO Primer must be allowed to dry for a minimum of 30 minutes at 21°C prior to the application of Sika-Ceram adhesives or waterproofing membranes, self-levelling compounds. This is dependent on substrate porosity, ambient temperature and relative humidity.
<b>Limitations</b>	<ul style="list-style-type: none"><li>■ Sikafloor Level PRO Primer must not be diluted under any circumstances</li><li>■ Sikafloor Level PRO Primer is not suitable for use over non-porous concrete</li><li>■ Sikafloor Level PRO Primer is not suitable for use over existing tiles and waterproofing membranes</li><li>■ Sikafloor Level PRO Primer is not suitable for use over non-porous substrates including metal, plastic glass or other similar impervious substrates</li><li>■ Do not apply onto wet or damp substrates</li><li>■ Do not apply in temperatures below 5°C or over 35°C and under hot and windy conditions</li></ul>

<b>Cleaning</b>	Sikafloor Level PRO Primer can be cleaned up using water before the product dries.
<b>Packaging</b>	20 Litre, 5 Litre and 1 Litre
<b>Form</b>	White Liquid
<b>Safety Directions</b>	Avoid contact with skin and eyes. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. No smoking. Avoid contact with foodstuffs, and sources of heat and ignition. Wash hands after use. Store in a cool place and out of direct sunlight. Store away from oxidising agents. Keep containers closed when not in use. Do not empty into drains. If involved in a fire, use water, fog, foam or dry agents. Avoid breathing products of combustion. Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up and place spilled material in clean, dry, sealed container. Flush spill area with water. If poisoning occurs, contact a doctor or Poisons Information Centre: Australia - 13 11 26, New Zealand - 0800 764 766. Do not reuse container unless thoroughly decontaminated. See the Sika Safety Data Sheet (SDS) for additional information. Contact 1800 033 111 (24/7) for emergency information. If swallowed, do not induce vomiting. Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Immediately irrigate with copious amount of water for 15 minutes if have come in contact with eyes. Eyelids to be held open. Urgently seek medical advice. If skin or hair contact occurs, flush skin and hair with running water and soap if available. Seek medical attention in event of irritation. If fumes or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. Seek medical advice if in doubt.
<b>Legal Notes</b>	The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



**Sika Australia Pty Limited**  
 ABN 12 001 342 329

**aus.sika.com**  
 Tel: 1300 22 33 48

