



TECHNICAL DATA SHEET

Econo-Mono

- **Compliance**
Econo-Mono complies to ASTM C 1116-10.
- **Product Description**
Econo-Mono is a medium duty fibre that offers good bonding, long term durability and improved toughness.
- **Applications**
Econo-Mono provides an excellent low dose, steel free crack control solution for house slabs, toppings, drive-ways, footpaths and most general purpose concrete slab on ground applications.
- **Benefits**
Econo-Mono is designed to provide excellent resistance to plastic and shrinkage cracking.
- **Material Properties**
100% virgin homopolymer polypropylene
- **Fibre Count**
32,000,000/kg
- **Form**
Monofilament fibre
- **Length**
19mm, 10mm and 13mm on request.
- **Specific Gravity**
0.91
- **Acid/Alkali Resistance**
Excellent
- **Tensile Strength**
600MPa
- **Packing and Storage**
Econo-Mono is packaged in:
 - 0.6kg mulchable bags
 - 30 x 0.6kg bags per box
 - 12 boxes per palletRecommended storage is a dry covered area
- **Performance**
Dose rate: 0.6kg/m³
- **Mixing Procedure**
Add fibres with additives. If assistance is required click on "Mixing Procedure" or contact TEXO directly.
- **Technical Advice**
If assistance with design or dose rates is required, please contact TEXO, our contact details are below.